


Product information

VITOLEN 120 Soft Spulen (bobbins)

Sealing-tape of polyolefin soft foam with partial open-cell structure, reinforced with polyolefin film. Not self-adhesive.


Product composition

Carrier, PO soft foam, anthracite
 Laminating adhesive
 Reinforcement, PO-film, transparent



Application

VITOLEN 120 Soft Spulen is used as sealing tape at the manufacturing of sandwich panels.



Product benefits

- Very soft foam
- Very good airtight seal by low compression
- Excellent thermal insulation
- Water repellent foam skin
- Easy to apply due to the reinforcement
- Odourless, plasticiser free

Technical data of foam

Thickness		5 mm	8 mm
Compressive strength (DIN EN ISO 3386-1)	at 50 % deformation	5 kPa	15 kPa
Compression set at 50 % deflection (ISO 1856-C)	0.5 h after discharge	17 %	18 %
	24 h after discharge	7 %	7 %
Thermal conductivity (ISO 8301)	at 10 °C	0.04 W/m·K	
	at 40 °C	0.04 W/m·K	
Water absorption (ISO 2896)		≤ 2 vol%	
Fire behaviour (DIN 4102-2)	burn distance < 150 mm	pass	
Fire behaviour (ISO 3795/FMVSS 302)	burning speed < 100 mm	pass	
Temperature resistance		-30 °C to 90 °C	

VITOLEN 120 Soft Spulen (bobbins)

Storage and shelf life

12 month after receipt of goods, when stored at room temperature ($20 \pm 3 \text{ }^\circ\text{C}$) and 40 - 60 % relative humidity out of direct sunlight, in original packaging.

Special Information

The data and technical information presented are characteristic or average data. All advices are given to the best of our knowledge. You are kindly requested to conduct your own tests to determine the suitability of our product for your application. Our General Conditions answer any questions on guarantees and liabilities for these products unless other legal regulations apply.

If you need further information about product safety, conformance, REACH or RoHS please send your e-mail to info@vito-irmen.de

version: 04/2018 Fi