


Product Information VITOMOUNT 140

Double-sided self-adhesive pressure-sensitive mounting tape.

Product composition



adhesive, modified acrylate
carrier, PE foam, anthracite, 0.4 mm
adhesive, modified acrylate
liner, siliconised paper, yellow

Application

VITOMOUNT 140 has been designed for bonding on low-energetic and rough surfaces. It is suitable to mount trim strips, faceplates, metal plates and plastics during assembly. The tape is used for self-adhesive finishing of profiles, cable ducts, displays and product samples.

Product benefits

- enables to mount two components with minimized gap
- excellent initial and good final adhesive strength
- conforms with rough and uneven surfaces
- no yellowing of the foam

Technical data

peel adhesion on steel acc. to DIN EN 1939:1996	at 20 °C	20 N / 25 mm
shear adhesion on steel acc. to DIN EN 1943:1996	at 20 °C	15 N / 625 mm ²
	at 50 °C	5 N / 625 mm ²

Product properties

temperature resistance	-40 °C to 90 °C
application temperature	15 °C bis 30 °C
ageing resistance	good
weathering resistance	good
compatible with acrylic glass	yes
chemical resistance	good

Processing

The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage and shelf life

12 month after receipt of goods, when stored at 18 °C and 60 % relative humidity protected from sunlight, in original packaging.

Special Information

The data and technical information presented are characteristic or average data. All advices are given to the best of our knowledge. You are kindly requested to conduct your own tests to determine the suitability of our product for your application. Our General Conditions answer any questions on guarantees and liabilities for these products unless other legal regulations apply.

If you need further information about product safety, conformance, REACH or RoHS please send your e-mail to info@vito-irmen.de

11/2014 ki