

Product information

VITOCOLL T 301

Transfer tape based on a paper fleece equipped with a modified acrylate on both sides.

Product composition



Adhesive, modified acrylate
Carrier, paper fleece
Adhesive, modified acrylate
Liner, siliconised paper, yellow-brown

Application

VITOCOLL T 301 is used for adhesion and lamination of decorative material, trims and fittings, displays and other adhesive applications.

Product benefit

- good adhesion on metal, polystyrene, plasticiser free and soft PVC, cellular rubber and cellular PE
- very good weathering and temperature resistance

Technical data and product properties

thickness	0.11 mm		
peel adhesion on stainless steel FINAT TM 1	at 23 °C	16 N / 25 mm 18 N / 25 mm 20 N / 25 mm	after 1 min after 20 min after 24 h
shear adhesion on stainless steel acc. to DIN EN 1943:1996	at 23 °C	10 N / 625 mm ²	
temperature resistance	-40 °C to 120 °C		
application temperature	15 °C to 30 °C		
weathering resistance	very good		

Processing

The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage and shelf life

12 month after receipt of goods, when stored at 18 °C and 60 % relative humidity protected from sunlight, in original packaging

Special Information

The data and technical information presented are characteristic or average data. All advices are given to the best of our knowledge. You are kindly requested to conduct your own tests to determine the suitability of our product for your application. Our General Conditions answer any questions on guarantees and liabilities for these products unless other legal regulations apply.

If you need further information about product safety, conformance, REACH or RoHS please send your e-mail to info@vito-irmen.de

05/2015 Ki