VITO Irmen GmbH & Co. KG



Product information VITOSEAL 100 PW "The Quick Roll" Single-sided self-adhesive sealing tape based on polyvinyl chloride foam (PVC). The siliconised paper acts as reinforcement and can be removed after applying the sealing tape.

adhesive, modified acrylate carrier, PVC foam, black ⁻ reinforcement, siliconised paper, white ⁻

Application

VITOSEAL 100 PW is used for all kinds of indoor and outdoor sealing applications.

Product benefits

- The elastic property of the foam enables very good conformance to all surfaces.
- The foam is self-extinguishing and has a very good UV resistance.
- Easy application without overexpansion.

Technical data foam

thickness	3, 4, 5, 6, 8 and 10 mm
density (DIN EN ISO 845)	100 - 125 kg/m³
compression deflection (ASTM 1667)	0 sec. 12 - 33 kPa 60 sec. 4 - 16 kPa
shore hardness 00	20 – 40
compression set (DIN 53572) 50 % / 23 °C / 72 h	≤ 45 %
waterabsorption	≤ 30 %
flammability (FMVSS 302)	\leq 100 mm/min (thickness \geq 6 mm)
compression waterseal (U-test)	30 %
thermal conductivitiy λ	0,052 W/m•K
UV resistance	very good
weathering resistance	good

 Phone:
 +49(0)2642/4007-0

 Fax:
 +49(0)2642/42913

 E-Mail:
 info@vito-irmen.de

 further information:
 www.vito-irmen.de





VITOSEAL 100 PW Product properties

compatible with acrylic glass or polycarbonate	no
temperature resistance	-30 °C to 60 °C
application temperature	15 °C to 30 °C

Processing

The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage and shelf life

6 months after receipt of goods, when stored at roomtemperature (20 \pm 3 °C) and 40 - 60 % relative humidity, protected from sunlight, in original packaging.

Special Information

The data and technical information presented are characteristic or average data. All advices are given to the best of our knowledge. We reserve the right to make technical changes that are in the interest of progress. You are kindly requested to conduct your own tests to determine the suitability of our product for your application. Our General Conditions answer any questions on guarantees and liabilities for these products unless other legal regulations apply.

If you need further information about product safety, conformance, REACH or RoHS please send your e-mail to <u>info@vito-irmen.de</u>

03/2019 Fi

