

## Product information

### VITO STRESSMOUNT RM 120 DSK PW

Double-sided self-adhesive coated polyethylene foam, appropriate for the use on skin.



## Product composition

**Adhesive**, modified acrylic PSA  
**Carrier**, PE-foam, white, 1 mm  
**Adhesive**, modified acrylic PSA  
**Liner**, siliconised paper, white, approx. 120 g/m<sup>2</sup>

## Application

The product is used to manufacture medical care products.

## Technical data and product properties

180° Peel adhesion on steel according to DIN EN 1939	foam failure
Loop-Tack on polypropylene, according to FINAT FTM 9	≥ 10 N / 25 mm
Temperature resistance	-40 °C to 70 °C
Sterilisation	with steam, UV-light and gamma radiation

## Storage and shelf life

12 months after receipt of goods, when stored at roomtemperature (20 ± 3 °C) and 40 - 60 % relative humidity, protected from sunlight, in original packaging.

### Special Information

The data and technical information presented are characteristic or average data. All advices are given to the best of our knowledge. We reserve the right to make technical changes that are in the interest of progress. You are kindly requested to conduct your own tests to determine the suitability of our product for your application. Our General Conditions answer any questions on guarantees and liabilities for these products unless other legal regulations apply.

If you need further information about product safety, conformance, REACH or RoHS please send your e-mail to [info@vito-irmen.de](mailto:info@vito-irmen.de)

06/2019 Fi