


# Preliminary product information VITOMOUNT A 3201

Double-sided self-adhesive foam tape for high standards.

# Product composition

Adhesive, Pure acrylic -Carrier, PE-foam, black -Adhesive, Pure acrylic -Liner, siliconised PP film, 70 μm, green -



# **Application**

VITOMOUNT A 3201 is designed for permanent attachment of materials with smooth or slightly uneven surfaces indoors and outdoors. It combines a variety of materials, including metals, high-energy plastics or composites. VITOMOUNT A 3201 has a very high peel and shear strength.

#### Product benefits

- High peel and shear strength
- Absorption of vibration
- Good aging, weathering and plasticizer resistance
- Compensation of slight unevenness and thermal expansion

# Technical data and product properties

thickness	0.5 mm / 0.8 mm / 1 mm
density	125 kg/m <sup>3</sup>
peel adhesion on stainless steel (180°) after 72h at 20°C	0.5 mm 35 N / 25 mm 0.8 mm 60 N / 25 mm 1.0 mm 55 N / 25 mm
peel adhesion on stainless steel (90°) after 72h at 20°C	0.5 mm 55 N / 25 mm 0.8 mm 95 N / 25 mm 1.0 mm 115 N / 25 mm
shear adhesion on stainless steel after 24h at 20°C	0.5 mm 0.8 mm 1.0 mm

Phone: +49(0)2642/4007-0
Fax: +49(0)2642/42913
E-Mail: info@vito-irmen.de
Further information: www.vito-irmen.de





### **VITOMOUNT A 3201**

## Technical data and product properties

temperature resistance	-40 °C to 90 °C
SAFT-Test (ASTM D-4498) 625 mm², 500 g, 30 °C / h	164 °C
application temperature	15 °C to 30 °C

# **Processing**

The most important processing parameters and information about cleaning are listed in our Information on Processing Adhesive Tapes.

### Storage and shelf life

12 months after receipt of goods, when stored at room temperature (20  $\pm$  3 °C) and 40 - 60 % relative humidity, protected from sunlight, in original packaging.

#### Special Information

The data and technical information presented are characteristic or average data. All advices are given to the best of our knowledge. You are kindly requested to conduct your own tests to determine the suitability of our product for your application. Our General Conditions answer any questions on guarantees and liabilities for these products unless other legal regulations apply.

If you need further information about product safety, conformance, REACH or RoHS please send an e-mail to info@vito-irmen.de

Phone: +49(0)2642/4007-0

E-Mail: <u>info@vito-irmen.de</u>

+49(0)2642/42913

Further information: www.vito-irmen.de

version: 11/2019 MB

